



## AisleLok<sup>®</sup> Acrycell<sup>™</sup> Sealing Tape

### Part Number

10108-001 ACRYCELL SEALING TAPE, .5"H x .71"W x 26.25'L, BLACK, 3 ROLLS

10108-002 ACRYCELL SEALING TAPE, 1"H x .71"W x 14.1'L, BLACK, 3 ROLLS

10108-003 ACRYCELL SEALING TAPE, .2"H x 1.18"W x 8.5'L, BLACK, 5 ROLLS



1" Acrycell Sealing Tape  
Part No. 10108-002

### Application

The AisleLok<sup>®</sup> Acrycell Sealing Tape is the premium choice for sealing unusual gaps and openings in the data center including:

- Room perimeter.
- Floor openings.
- Under cabinets.
- Between racks.
- Around CRAC units.

Its revolutionary sealing technology greatly reduces costly bypass airflow, increasing usable cooling unit capacity, and ensuring maximized efficiency from HVAC equipment.

### Features

- Non-particulating tape is safe for the data center and ensures a durable secure seal .
- AisleLok<sup>®</sup> products are compliant with directive 2002/95/EC of the European Parliament and the Council on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electric Equipment (RoHS).
- Time release expansion allows product installation without disturbing cables; tape will fully expand within 72 hours or longer depending on ambient temperature.
- Conforms to non-uniform spaces when completely expanded.
- Compact size for easy portability.

### Benefits

- Supports increasing cabinet density.
- Increases existing cooling unit capacity.
- Reduces the need to purchase additional cooling units.
- Improves IT equipment reliability and extends equipment life.

### Unique Acrycell Technology

Confirmed by a 3rd party laboratory's accelerated aging test this non-particulating sealing tape is truly "Data Center Safe" and also offers:

- Time release expansion that ensures a tight seal around cables and other impediments.
- Moldable physical quality that forms a tight seal on uneven surfaces and gaps.
- Customizable tape unrolls creating one continuous and uniform top-to-bottom seal.
- "Peel and Stick" installation saves labor, time and money.
- Compressed tape eliminates pinching, stuffing, or otherwise manipulating to install.

## Specifications

Part Number	Expansion Size	Rolls in Carton	Compressed Tape Minimum Effective Thickness	Expanded Tape Maximum Effective Thickness	Tape Width	Roll Length
10108-001	.5" (13mm)	3	.12" (3mm)	.60" (15mm) ± 10%	.71" (18mm)	26.25' (8m)
10108-002	1" (25mm)	3	.20" (5mm)	1.22" (31mm) ± 10%	.71" (18mm)	14.1' (4.3m)
10108-003	2" (50mm)	5	.35" (9mm)	2.0" (51mm) ± 10%	1.18" (30mm)	8.5' (2.6m)


### Data Center Safe Sealing System

Confirmed "Data Center Safe", the non-particulating, time release Acrycell sealing technology is designed to seal gaps against racks, cabinets or other enclosures in the mission critical data center environment.


### Sealing Effectiveness

Acrycell sealing technology has been engineered to fill gaps tightly against airflow and particulates across a wide spectrum of widths. Confidently and cost effectively sealing gaps against errant airflow ranging from 5 to 50mm in width, between racks, cabinets, or other data center equipment.

### Product Drawings



.5" Acrycell Sealing Tape



### Temperature Resistance

Durable Acrycell sealing tape is both temperature resistant from -40 to 212°F (-40 to 100°C) and fire resistant to DIN 4102 Class B1.

Finish: Black

### Mounting System

Adhesive mounting system consisting of:

- Single-sided, pressure sensitive tape with durable and field tested adhesive backing.



888-982-7800

sales@upsite.com