

KoldLok® Integral Raised Floor Grommet

Part Number

1010 Integral Grommet

3030 Split Integral Grommet



Applications

Designed to seal openings in new raised floor cutouts prior to the installation of communications or power cabling. Based on measurements at multiple data centers, on average 60% of valuable conditioned air is not reaching the air intake of IT equipment due to unsealed floor openings. This lost air, known as bypass airflow, contributes to IT equipment hot spots, cooling unit inefficiencies, and increasing infrastructure costs. KoldLok® products specifically address bypass airflow and its detrimental effects on data center cooling.

Benefits

- Increases existing cooling unit capacity
- Reduces the need to purchase additional cooling units
- Improves equipment reliability and extends equipment life
- Increases static pressure under the raised floor and improves cool air delivery through perforated tiles and floor grates
- Facilitates Cold Aisle/Hot Aisle best practices

Features

- The Split Integral Grommets allow tiles to be moved without capturing cables
- The Grommets contain no loose or partially fastened parts, which can become separated or fall through the raised floor
- The Grommets are impact resistant and durable
- The Grommets satisfy NFPA 75 Section 5-4.4 requirement by self-dressing the raw metal edges of raised floor tile cable cutouts
- KoldLok® products are compliant with Directive 2002/95/EC of the European Parliament and the Council on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment (RoHS)

Sealing Effectiveness

- Effective bypass-airflow sealing in areas undisturbed by cable penetrations at static pressures up to 0.10 inches of water column
- Effective bypass-airflow sealing with four, half-inch cables penetrating the Grommet at a static pressure of 0.10 inches of water column

SPECIFICATIONS

| Part Number | Description | Dimensions | Quantity per Carton | Shipping Weight |
|-------------|-----------------------------------|---|---------------------|-----------------|
| 1010 | Raised Floor Brush Grommet | 11" x 8.25" x 1.625" (279 mm x 210 mm x 41 mm) | 10 | 16 lbs. |
| 3030 | Raised Floor Brush Grommet, Split | 11" x 8.25" x 1.625" (279 mm x 210 mm x 41 mm) | 10 | 16 lbs. |

Patented Sealing System


U.S. Patent No. RE41863 and International Patents Pending for multi-layer, opposing and interwoven filaments.

Grommet Frame

Four (4) self-drilling screws are provided for installation


The Integral Raised Floor Grommet frame is molded from durable polypropylene. The Split Integral Raised Floor Grommet frame also consists of two, interlocking polypropylene halves.
Finish: Black

KoldLok® Integral Raised Floor Grommet



Raised Floor Tile

KoldLok® Split Integral Raised Floor Grommet



Raised Floor Tile